

IMPORTANT CARE INSTRUCTIONS

Polymag Tek™ Adhesive Tape & Pads are manufactured to provide our customers with the highest level of cleaning of any contact cleaning rolls. To ensure maximum performance from our Tape & Pads the following suggestions should be adhered to.

- 1. Store and use adhesive products between 70°F and 40°F and a relative humidity of 50%**
- 2. Adhesive rolls should be transported and stored vertically to prevent flat spots.**
- 3. Use adhesive products within one year of receipt for maximum performance.**

Adhesive Rolls

- Special white coated paper totally cleans contact cleaning rolls.
- Uniform adhesive coating with excellent wind quality.
- Interchangeable with other clean machines.

Adhesive Pads

- Convenient 9" x 13" size.
- Special white adhesive coated paper totally removes dirt from the rollers.
- No adhesive transfer to the rollers.
- 50 sheets per pad, 5 pads/case

Hand Held Contact Cleaning Rollers (HCCR)

- Removes particles down to 1 micron size.
- Custom fit handle eliminates the need for an expensive pad holder.
- Stainless steel construction for durability.



NO MORE DIRT!

Eliminate contamination with these new products...

Polymag Tek 4 Roll Sheet Cleaner

FEATURES

- Clean room design.
- Removes particles to 1 micron.
- Large capacity up to 60" wide.
- Convenient controls.
- Made in USA for fast spare part needs.
- Durable large footprint of contact cleaning rolls on substrate to enhance cleaning efficiency.
- Variable speeds: 25 to 100 FPM.
- Quick release mechanism for changing of adhesive tape rolls & contact cleaning rolls.
- Two sided static elimination available.
- In-feed and out-feed conveyors.

APPLICATIONS

- Clean separator/caul plates before lay up.
- Clean sheet or roll stock .01 to .500 thick.
- Clean sheets or panels before packaging/shipping



Patent #'s 6006843, 5855172

Thin Film Sheet Cleaner



Patent # 5913345

FEATURES

- Removes particles to 1 micron.
- Cleans sheets as thin as .001.
- Variable speed 10 to 100 FPM.
- 110 VAC Power & 60 PSIG.
- Two sided static elimination.
- Can be customized to fit your application.

APPLICATIONS

- Clean pre-preg before lay up.
- Clean lamination plates.
- Clean inner layers before AOI.
- Clean any thin sheet material down to .001 requiring removal of loose contamination.
- Clean panels before exposure.

*Call for custom
solutions for
your applications!*



1-800-787-0830
www.polymagtek.com
email: info@polymagtek.com